

Antenne interne telefonia e accessori

Mobile phone indoor antennas and accessories

GSM - DCS - UMTS

Antenne interne, cavi ed accessori da utilizzare in abbinamento alle antenne log periodic per esterno, per la creazione di ponti freddi. Sono particolarmente adatti per l'estensione dei segnali di telefonia mobile o per risolvere problematiche di assenza di segnale all'interno degli edifici (senza amplificare).

Indoor antennas, cables and accessories to be used together with outdoor log periodic antennas.

They are especially suitable for the extension of mobile phone signals or to solve problems of absence of signal inside buildings (without boost).

codice code	descrizione description
1SGSM	Antenna stilo da interno per segnali GSM(890 - 960 MHz). •Tipologia: Antenna omnidirezionale interna •Polarizzazione: Verticale •Guadagno: 2.5 dBi •Dimensioni: 215 x 50 x 48 mm •Peso: 330 gr •Adattatore N maschio / SMA femmina <i>Indoor antenna for GSM signals (890 - 960 MHz).</i> •Type: omnidirectional indoor antenna •Polarization: Vertical •Gain: 2.5 dBi •Dimensions: 215 x 50 x 48 mm •Weight: 330 gr •N male / SMA female adapter
1PGSM	Antenna pannello GSM - DCS - UMTS. L'antenna patch presenta un elevato guadagno nella direzione della Base Station permettendo la connessione dove le distanze sono significative. Le piccole dimensioni e il contenuto impatto ambientale la rendono una perfetta soluzione per l'uso esterno in banda GSM (900 e 1800 MHz), DCS e UMTS. •Tipologia: Antenna direttiva esterna/interna •Polarizzazione: Verticale •Radiazione: Piano H 360° •Guadagno: 9 dBi •Dimensioni: 170 x 155 x 75 mm •Peso: 580 gr •Connettore: N maschio <i>Patch antenna for GSM-DCS-UMTS. The patch antenna has a high gain in the direction of the Base Station allowing the connection where the distances are significant. The small size and low environmental impact make it a perfect solution for outdoor use in band GSM (900 and 1800 MHz), DCS and UMTS.</i> •Type: Directional Antenna outdoor/indoor •Polarization: Vertical •Radiation: Plan H 360° •Gain: 9 dBi •Size: 170 x 155 x 75 mm •Weight: 580 gr •Connector: N male
805C5	Cavo 50 Ohm preintestato N mas./ SMA mas. Matassina da 5 m <i>50 Ohm cable with N male/SMA male connectors. Cable length: 5 mt</i>
805C10	Cavo 50 Ohm preintestato N mas./ SMA mas. Matassina da 10 m <i>50 Ohm cable with N male/SMA male connectors. Cable length: 10 mt</i>
805C15	Cavo 50 Ohm preintestato N mas./ SMA mas. Matassina da 15 m <i>50 Ohm cable with N male/SMA male connectors. Cable length: 15 mt</i>
805FME	Adattatore FME mas. / N mas. Da abbinare a 16GSM e 1SGSM per realizzare ponte freddo. <i>FME male / N male adaptor. To use with 16GSM and 1SGSM to extend mobile phone signals.</i>

